Preliminary Amendment – Sick et al.

International Application No. PCT/EP2005/003166

Filed: 24 March 2005

Page 4

Amendments to the Claims (As Amended to Incorporate the Article 34 Amendments):

Please substitute pages 14-16 as originally filed with the attached amended pages 14-16. These new pages incorporate revisions to the international PCT application which were modified under Article 34. Then,

Before claim 1 on amended page 14 insert -- We claim:--

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) Soil compacting device, havingcomprising:
- a common upper mass (1)-having a drive[5;] and having
- at least two lower masses $\frac{(2)}{}$ that are coupled to the upper mass $\frac{(1)}{}$ and that are capable
of oscillatory movement relative to the upper mass-(1),
each lower mass having:
a soil contact plate (6)-and
at least one vibration exciter (7)-that is allocated to the soil contact plate-(6) and
that is driven by the drive,
characterized in that
the vibration exciters (7) are capable of being driven by the drive provided on the upper
mass (1).

2. (Currently Amended) <u>SA soil</u> compacting device as recited in Claim 1, <u>characterized in that wherein the vibration exciters (7) have two or more imbalance</u>

{00109497.DOC/}

Your Ref.: WW_AZ_0000238Pat/mi

Our Ref.: 72.112

Preliminary Amendment – Sick et al. International Application No. PCT/EP2005/003166

Filed: 24 March 2005

Page 5

shafts-(8), each bearing one or more imbalance masses, that are situated parallel to one another or at an angle to one another, and are capable of rotation in opposite directions to

one another.

3. (Currently Amended) <u>SA soil</u> compacting device as recited in Claim 1-or 2,

eharacterized in that wherein at least one of the vibration exciters (7) has a phase

adjustment device for adjusting the relative phase position of the imbalance shafts (8)-to

one another.

4. (Currently Amended) Soil compacting device as recited in one of Claim[s] 1-to-3,

characterized in that wherein exactly one vibration exciter (7) is situated on each soil

contact plate (6).

5. (Currently Amended) <u>SA soil</u> compacting device as recited in one of Claim[s] 1

to 4, characterized in that wherein a resultant propulsive force in a direction of

propulsion can be produced at least by one of the vibration exciters (7).

6. (Currently Amended) SA soil compacting device as recited in one of Claim[s] 1

to-5, characterized in that wherein at least one of the vibration exciters (7) is situated in

such a way that the horizontal component of the resultant force vector resulting from the

imbalance shafts (8) rotating in opposite directions to one another is oriented in or

opposite to a main direction (A).

7. (Currently Amended) SA soil compacting device as recited in one of Claim[s] 1

to 6, characterized in that wherein at least one of the vibration exciters (7) is situated in

such a way that the horizontal component of the resultant force vector that results from

the imbalance shafts (8) rotating in opposite directions is not oriented in or opposite to a

main direction (A).

Preliminary Amendment – Sick et al. International Application No. PCT/EP2005/003166

Filed: 24 March 2005

Page 6

8. (Currently Amended) <u>SA soil</u> compacting device as recited in <u>one of Claim[s]</u> 1 to 5, or as recited in Claim 7 in connection with one of Claims 1 to 5, characterized in that wherein none of the vibration exciters (7) is situated in such a way that the horizontal component of the resultant force vector that results from the imbalance shafts (8) rotating in opposite directions is oriented in or opposite to a main direction (A).

- 9. (Currently Amended) <u>SA</u> soil compacting device as recited in <u>one of Claim[s]</u> 1 to 8, <u>characterized in that wherein</u> at least one of the vibration exciters (7) is situated in such a way that the horizontal component of the resulting force vector that results from the imbalance shafts (8) rotating in opposite directions is oriented at a particular angle to a main direction (A).
- 10. (Currently Amended) <u>SA</u> soil compacting device as recited in Claim 9, characterized in that wherein the angle is 60° or 90°.
- 11. (Currently Amended) <u>SA soil</u> compacting device as recited in <u>one of Claim[s]</u> 1 to 10, <u>characterized in that wherein</u> the upper mass (1) has a central control unit for controlling the vibration exciters (7).
- 12. (Currently Amended) SA soil compacting device as recited in Claim 11, characterized in that wherein the vibration exciters (7) are capable of being controlled individually by the control unit.
- 13. (Currently Amended) <u>SA soil</u> compacting device as recited in Claim 11-or-12, eharacterized in that wherein the control unit is fashioned for the setting of different rotational speeds of the imbalance shafts (8) in different vibration exciters (7).

{00109497.DOC/}

Your Ref.: WW AZ 0000238Pat/mi

Our Ref.: 72.112

Preliminary Amendment – Sick et al. International Application No. PCT/EP2005/003166

Filed: 24 March 2005

Page 7

14. (Currently Amended) <u>SA soil compacting device as recited in one of Claim[s]</u> 11

to 13, characterized in that wherein the control unit is fashioned for the individual

controlling of the phase adjustment devices provided on the individual vibration exciters

(7).

15. (Currently Amended) <u>SA soil compacting device as recited in one of Claim[s] 1</u>

to 14, characterized in that wherein a part of the lower masses (2) each has a vibration

exciter (7) having a phase adjustment device, while at least one other lower mass (2) has

only a vibration exciter-(7) that does not have a phase adjustment device.

16. (Currently Amended) <u>SA soil</u> compacting device as recited in one of Claim[s] 1

to 15, characterized in that wherein the soil compacting device can be guided by hand

and/or has a remote control device.

17. (Currently Amended) SA soil compacting device as recited in one of Claim[s] 1

to 16, characterized in that wherein the soil contact plates (6) of the imbalance masses

(22) arc situated so as to be offset to one another in such a way that the tracks that can be

produced on the soil that is to be compacted during movement of the soil compacting

device in at least one main direction of travel overlap at least partially.

{00109497.DOC/}

Your Ref.: WW_AZ_0000238Pat/mi

Our Ref.: 72.112